

High-Quality Illumination at an Exceptional Value

The BLC troffer by Lithonia Lighting® delivers soft, glare-free, ambient lighting in a popular center-basket design. The slim profile of the luminaire, coupled with energy-saving LED technology make BLC the ideal choice for renovation or new construction.

The BLC LED troffer enhances the visual environment by creating a balance between task illuminance and spatial brightness.

The resulting "volumetric" effect increases the perceived lighting level, improves visual comfort and reinforces a sense of occupant security and wellbeing. The BLC troffer offers a high-quality, cost-effective LED lighting solution for schools, offices, retail, healthcare facilities and other commercial spaces.



Key Features:

- Available in 2' x 2' and 2' x 4' configurations
- Contractor Select[™] BLC options for the most popular and readily available configurations
- Slim 2-3/8" profile fits restrictive plenums and optimizes pallet space
- Dims to 10%
- Long-life LEDs deliver 80% lumen maintenance at 60,000 hours

BLC Series LED Luminaire

Ordering Information

	BLC Series Stock Solutions						
	Description	Model	CI Code	UPC Code	Wattage	Pallet Quantity	
2'x2' BLC LED	2'x 2' BLC, 3300 Lumens, 3500K	BLC 2X2 3300LM 35K	*2515T6	191848536469	32W	52	CS
	2'x 2' BLC, 3300 Lumens, 4000K	BLC 2X2 3300LM 40K	*2515T8	191848536506	32W	52	CS
	2'x 2' BLC, 3300 Lumens, 5000K	BLC 2X2 3300LM 50K	*2515TA	191848536520	32W	52	
	2'x 2' BLC, 4000 Lumens, 3500K	BLC 2X2 4000LM 35K	*2515TE	191848536544	39W	52	CS
	2'x 2' BLC, 4000 Lumens, 4000K	BLC 2X2 4000LM 40K	*2515TF	191848536551	39W	52	CS
	2'x 2' BLC, 4000 Lumens, 5000K	BLC 2X2 4000LM 50K	*2515TG	191848536568	39W	52	
2'x4' BLC LED	2'x 4' BLC, 4000 Lumens, 3500K	BLC 2X4 4000LM 35K	*2515TH	191848536575	37W	26	CS
	2'x 4' BLC, 4000 Lumens, 4000K	BLC 2X4 4000LM 40K	*2515TJ	191848536629	37W	26	CS
	2'x 4' BLC, 4000 Lumens, 5000K	BLC 2X4 4000LM 50K	*2515TK	191848536612	37W	26	
	2'x 4' BLC, 5000 Lumens, 3500K	BLC 2X4 5000LM 35K	*2515TL	191848536636	49W	26	CS
	2'x 4' BLC, 5000 Lumens, 4000K	BLC 2X4 5000LM 40K	*2515TN	191848536599	49W	26	CS
	2'x 4' BLC, 5000 Lumens, 5000K	BLC 2X4 5000LM 50K	*2515TP	191848536605	49W	26	

