



Catalog Number
Notes
Type

Contractor Select™

# FMMLS 7

## Versi Lite™ LED Switchable Flush Mount



The LED Versi Lite Flush Mount offers an energy-efficient lighting solution for an array of indoor and outdoor residential and light commercial spaces. With a 50,000 hour maintenance-free life, the Versi Lite delivers reliability along with bright, high quality illumination. Ideal for use in closets, foyers, hallways, bedrooms, offices, utility work areas, stairways, and many other rooms in the house.

**FEATURES:**

- 30K/40K/50K CCT Switchable
- Dimmable to 10% on most standard triac dimmers
- 90+ CRI



Catalog Number	UPC	Description	Replaces up to	Lumens	Input Watts	CCT	Voltage	Pallet qty.
FMMLS 7 SWW2 M6	00193048277456	7" Switchable Versi Lite	60W Incandescent	695	12.2	30K/40K/50K	120V	270



## Specifications

### INTENDED USE:

Provides general illumination in commercial and residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, outdoor covered areas, stairways and much more. Suitable for use within closet storage spaces when installed per NEC requirements.

### CONSTRUCTION:

This contemporary shaped fixture features a matte white acrylic diffuser on the round versions, and a robust aluminum housing.

### OPTICS:

50,000 hours life. Rated for 50,000 hours at >70% lumen maintenance. 90+ CRI  
3000 K: 636 lumens  
4000 K: 695 lumens  
5000 K: 656 lumens  
Factory set at 3000K CCT

### ELECTRICAL:

Fixture operates at 120 volts, 50/60 Hz. 7" Round standard input = 12.2 watts.  
Works with most standard incandescent dimmers.

### LISTINGS:

All sizes are CSA certified for sale in the USA and Canada. Also certified for Damp Location. ENERGY STAR® certified. Round Versi U.S. Patent No. D691,763  
Certified to the high efficacy requirements of California T24 JA8-2019

### WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.


## Dimensions

7"

Height: 1-3/4 (4.4)

Width: 7-1/4 (18.4)

Weight: 1.1lbs (.5 kg)



All dimensions are inches (centimeters) unless otherwise indicated.