

FEATURES & SPECIFICATIONS

INTENDED USE

Provides an LED lighting platform to deliver general or task lighting for residential and light commercial applications. Light engine delivers long life and excellent color to ensure a quality, low-maintenance light installation. Ideal for use in bathrooms, lavatories, hallways, corridors, stairways, utility areas and more.

CONSTRUCTION

The Traditional Square Vanity is constructed of an acrylic diffuser with housing available in brushed nickel. The white acrylic diffuser provides even illumination and softens the appearance of the LEDs for improved aesthetics.

OPTICS

2' produces 1300 lumens and 3' produces 1900 lumens at 3000K with 50,000 hours of life.

Extruded acrylic diffuser is of highly transmissive material to minimize LED image and provides highangle brightness control.

ELECTRICAL

Long-life LEDs, coupled with a multivolt driver, provide extended service life. Standard input = 9.5 watts, (2'); 26 watts, (3'). Fixture is rated to deliver L70 performance at 50,000 hours and operates at 120-277 volts.

Use with non-dimmable switches only.

LISTINGS

UL Listed to US and Canadian safety standards. Listed for damp locations. ENERGY STAR® certified.


WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at www.acuitybrands.com/support/warranty/terms-and-conditions

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

SPECIFICATIONS	2FT	3FT	
Length:	23-7/16 (595)	35-1/4 (895)	
Weight:	7.3 (3.3)	10 (4.5)	
3000K Lumens (LPW)	1302 (72)	1919 (73)	


 $All\ dimensions\ are\ inches\ (millimeters)\ unless\ otherwise\ indicated.\ Weights\ are\ pounds\ (kilograms).$



Decorative Indoor

Traditional Square Vanity





ORDERING INFORMATION For shortest lead times, configure product using bolded options .			Example: FMVTSL 36IN MVOLT 30K 90CRI BN			
Series		Length	Voltage	Color temperature	CRI	Finish
FMVTSL	Traditional Square Vanity	24IN 2' Nominal 36IN 3' Nominal	MVOLT MVOLT (120V-277V)	30K 3000 K	90CRI >90	BN Brushed Nickel

DECORATIVE INDOOR FMYTSL

LIGHTING FACTS



